	<sup>®</sup>	TELEPHC	NE NU	MBER		ZARD RATING		\	
FOR QUALITY, VALUE AND PERFORMANCE		Reg 206-6		3 = I	HIGH		REACTIVITY		
AUMOR.		For Emerge				MODERATE SLIGHT		$\checkmark$	
KLEENCO PRODUCTS, INC. • P.O. BOX 1786 • Bellevue, WA. 98009		Call Infotrac	35-5053	0 = 1 <b>*</b> = 3	SLIGHT NSIGNIFICANT SEE SECTION	v 🗸	;IAL		
MATERIAL SAFETY DATA SHEET									
PRODUCT NAME		DA		TE ISSUED 07-12-95		CODE	DOT HAZARD		
CITRAQUIK APC			PREPARED B			ale R. Silbaugh	003-0259	Not Regulated	
FORMULA Proprietary CHEMICAL NAMES AND OR SYNONYMS Compound Cleaning Liquid									
I - COMPOSITIONAL INFORMATION/SARA III INFORMATION									
INGREDIENTS		CAS NUMBER		OCCUPATION EXPOSURE LIMITS OSHA PEL ACGIH TLV OTHER			VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT	
Propylene Glycol n-Butyl Ether		005131-66-8 None				4.8 77° F.	-		
		015821-83-7							
No toxic chemical(s) subject to the reporting requirements of section 313 of Tittle III and 40 CFR 342. NOTE: The precise composition of this mixture is proprietary. A more complete description will be provided to a physician in the event of a medical emergency.									
II - PHYSICAL PROPERTY INFORMATION									
APPEARANCE and ODOR Water thin, clear orange liquid.									
MELTING POINT BOILING		NT	COATING V.O.C.			EVAPORATION RATE			
		4° F.	()	Not Applicable		Slower than ether			
SOLUBILITY IN WATER Miscible	RAVITY (VVater =	VITY (Water = 1)		VAPOR DENSITY Not Applicable					
III - FIRE AND EXPLOSION HAZARD INFORMATION									
FLASH POINT	ON TEMPERATU	N TEMPERATURE		LOWER EXPLOSION LIMIT (%)		UPPER EXPL	UPPER EXPLOSION LIMIT (%)		
		t Available		Not Applicable		Not App	Not Applicable		
EXTINGUISHING MEDIA									
SPECIAL FIRE FIGHTING PROCEDURES For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment. This may include self-contained breathing apparatus to protect against the hazardous effects of normal products of combustion or oxygen deficiency. Read the entire MSDS.									
UNUSUAL FIRE AND EXPLOSION HAZARDS None known									
IV - HEALTH HAZARD INFORMATION									
THRESHOLD LIMIT VALUE ROUTE			HALATION						
Not Established OF EN	Not Established OF ENTRY: A See H		ee Health Hazards			Hazards	See Health F	lazards	
HEALTH HAZARDS (Acute and Chronic) CHRONIC EFFECTS OF EXPOSURE: None known *See Section IX.									
CARCINOGENICITY: NTP			graphs OSHA Regulated						
Not considered to be a carcinogen				-	X				
SIGNS AND SYMPTOMS OF EXPOSURE INHALATION: Vapors and mist can cause the following: - headache - nausea - irritation of nose, throat, and lungs. EYE CONTACT: Direct contact with the material may irritate the eyes. SKIN CONTACT: Prolonged or repeated contact may irritate the skin.									
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE None Known.									
EMERGENCY AND FIRST AID PROCEDURES EYES: If this chemical contacts the eyes, promptly wash the eyes with large amounts of water, occasionally lifting the lower and upper lids. Get medical attention if any discomfort continues. Contact lenses should not be worn when working with this chemical. SKIN: If this chemical contacts the skin, flush the contaminated									
upper lids. Get medical attention if any discomfort skin with water. Where there is evidence of skin	continues. Contac	t lenses should not be	worn when	s, promptly Wa working with th person breathe	nis cher	eyes with large amou nical. SKIN: If this cher amounts of this cher	nis of water, occasionall nical contacts the skin, fl nical move the exposed	y muny the lower and ush the contaminated person to fresh air at	
once. Other measures are usually unnecessary.	INGESTION: If th	is chemical has been	swallowed	get medical a	ittentior	immediately.			

V - REACTIVITY INFORMATION								
X STABLE UNSTABLE CONDITIONS TO AVOID None								
HAZARDOUS DECOMPOSITION PRODUCTS May liberate carbon monoxide or carbon dioxide.								
HAZARDOUS MAY WILL NOT CONDITIONS TO AVOID POLYMERIZATION OCCUR X OCCUR Heat, sparks and open flame.								
INCOMPATIBILITY (Materials to avoid) Acids, oxidizing materials.								
VI - SPILL OR LEAK PROCEDURE INFORMATION								
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Stop the source of leak or release. Clean up releases as soon as possible, observing precautions in Special Protective Information. Contain liquid to prevent further contamination of soil, surface water or groundwater. Clean up small spills using appropriate techniques such as sorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Follow prescribed procedures for reporting and responding to larger releases.								
WASTE DISPOSAL METHODS Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations. Contact local environmental authorities for approved disposal of this material.								
VII - SPECIAL PROTECTION INFORMATION								
VENTILATION TYPE Local mechanical exhaust ventilation, capable of maintaining emissions at the point of use below the PEL.								
<b>RESPIRATORY PROTECTION</b> Wear a NIOSH-Approved respirator, appropriate for the concentration of vapor or mist encountered at the point of use.								
PROTECTIVE GLOVES     Impervious     EYE PROTECTION     Wear eye protection to prevent any reasonable probability of eye contact.								
OTHER PROTECTIVE EQUIPMENT Wear appropriate equipment to prevent any repeated or prolonged skin contact.								
VIII - STORAGE AND HANDLING INFORMATION								
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE Keep out of reach of children. Store in a cool dry place away from incompatible materials. Keep container tightly closed when not in use. Workers should wash promptly when skin becomes wet. The following equipment should be available: Eyewash. It is generally recognized that contact lenses should not be worn when working with chemicals because contact lenses may contribute to the severity of the injury.								
OTHER PRECAUTIONS Read and follow label instructions. The label contains information necessary for the proper use of the product. Containers, even those that have been emptied,								
will retain product residue and vapors. Always obey hazard warnings and handle empty containers as if they were full.								
IX - TOXICITY INFORMATION								
*HEALTH HAZARDS for Propylene Glycol n-Butyl Ether. INHALATION: Excessive exposure may cause irritation to upper respiratory tract. A single prolonged (hours) excessive inhalation exposure may cause adverse effects. Signs and symptoms of excessive exposure may be central nervous system effects. EYE CONTACT: May cause moderate eye irritation. May cause moderate corneal injury. SKIN CONTACT: Prolonged or repeated exposure may cause skin irritation. SKIN ABSORPTION: A single prolonged exposure may result in the material being absorbed in harmful amounts. The LD50 for skin absorption in rabbits is 1400 mg/kg. The liquid is reported to cause a burning sensation and itchiness at site of contact. Exposure to large amounts may produce anesthetic or narcotic effects. INGESTION: Single dose oral toxicity is low. The oral LD50 for rats is 3300 mg/kg. Small amounts swallowed incidental to normal handling operations are not likely to cause injury; swallowing amounts larger than that may cause injury. SYSTEMIC (OTHER TARGET ORGAN) EFFECTS: Observations in animals include only increase liver size following repeated exposure. TERATOLOGY (BIRTH DEFECTS): Birth defects are unlikely. Exposures having no adverse effects on the mother should have no effect on the fetus. REPRODUCTIVE EFFECTS: In animal studies, has been shown not to interfere with reproduction. MUTAGENICITY (EFFECTS ON GENETIC MATERIAL): Results of in vitro ('test tube') mutagenicity tests have been negative.								
X - MISCELLANEOUS INFORMATION								
Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and the removal of the material from eyes, skin and clothing.								
PRODUCT CODE NA = NOT AVAILABLE DATE OF ISSUE SUPERSEDES SIGNED   003-0259 07-12-95 Any Previous MSDS Image: Constraint of the con								
The information contained herein is based on data considered accurate. However no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained thereof. They are offered solely for your consideration, investigation, and verification. Any use of these data and information must be determined by the user to be in accordance with applicable Federal, State and Local laws and regulations. KLEENCO PRODUCTS, INCORPORATED and its Distributors assume no responsibility for personal injury or property damage to vendees, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of the material.								
PAGE 2 - 003-0259								