

KLEENCO PRODUCTS, INC.
• P.O. BOX 1786 • Bellevue, WA. 98009

PRODUCT NAME

TELEPHONE NUMBER Reg. Phone 206-641-8888

For Emergency Assitance Call Infotrac (800) 535-5053 1 = SLIGHT 0 = INSIGNIFICANT * = SEE SECTION IV

HAZARD RATING	FIRE /
4 = EXTREME	0 REACTIVITY
3 = HIGH	
2 = MODERATE	\ `\\ '\
1 = SLIGHT 0 = INSIGNIFICANT	CITY 0
U = INSIGNIFICANI	SPECIAL

CODE

DOT HAZARD

MATERIAL SAFETY DATA SHEET

DATE ISSUED

DURA-COTE			PR	PREPARED BY Dale R. Silbaugh 012-0039					Not Regulated	
FORMULA Proprietary	(CHEMICAL NAMES AND	OR SY	NONYMS		nd Cleaning Liquic	d d			
I-COM	1POS	ITIONALINFORM	1ATI	ON/SA	•	<u> </u>		N		
INGREDIENTS CAS NUMBER			OCC	UPATION I	EXPOUSURE		VAP		WEIGHT PERCENT	
*Diethylene Glycol Monomethyl Ether Dipropylene Glycol Methyl Ether *Dibutyl Phthlate		1111-77-3 34590-94-8 84-74-2	None 100 P 5 MG	PM 10	one 00 PPM MG/M3	None 150 PPM None	0.1 68°F 0.6 77°F 0.0 68°F.		2.0 1.0	
*Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Tittle III and 40 CFR 342. NOTE: The precise composition of this mixture is proprietary. A more complete description will be provided to a physician in the event of a medical emergency.										
II-PHYSICAL PROPERTY INFORMATION										
APPEARANCE and ODOR Water thin, milky white liquid										
MELTING POINT NotApplicable	BOILIN	BOILING POINT 363° to 635° F.		COATING V.O.C. Not Applicable				EVAPORATION RATE Slower than ether		
SOLUBILITY IN WATER Complete	IC GRAVITY (Water = 1) 1.0	GRAVITY (Water = 1) V			VAPOR DENSITY Not Applicable					
III-FIRE AND EXPLOSION HAZARD INFORMATION										
FLASH POINT AUTO I		IGNITION TEMPERATURE		LOWER EXPLOSION LIMIT (%)		I LIMIT (%)	UPPER EXPLOSION LIMIT (%		SION LIMIT (%)	
Not Applicable		Not Available		NotApplicable				Not Applicable		
EXTINGUISHING MEDIA X FOAM X CO2 X DRY CHEMICAL X WATER SPRAY OTHER										
SPECIAL FIRE FIGHTING PROCEDURES For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment. This may include self-contained breathing apparatus to protect against the hazardous effects of normal products of combustion or oxygen deficiency. Read the entire MSDS.										
UNUSUAL FIRE AND EXPLOSION HAZARDS Noneknown										
		IV-HEALTH HAZ	ARD	INFOR	MATIC	N				
THRESHOLD LIMIT VALUE ROUTE Not Established OF ENT		X INHALATION See Health Hazards		X SKII	N e Health Haz	zards	Х	(INGESTION See Health Haz	zards	
HEALTH HAZARDS (Acute and Chronic) CHRONIC EFFECTS OF EXPOSURE: None known *See Section IX.										
CARCINOGENICITY: Not considered to be a carcinogen NTP IARC Monographs X OSHA Regulated										
SIGNS AND SYMPTOMS OF EXPOSUE contact with the material may irritate the eyes. See	RE INHA (IN CONT	LATION: Vapors and mist can ca 'ACT: Prolonged or repeated co	ause the entact ma	following: - he ay irritate the	adache - nau skin.	usea - irritation of n	iose, tl	nroat, and lungs. EY	E CONTACT: Direct	
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE None Known.										
EMERGENCY AND FIRST AID PROCEDURES EYES: If this chemical contacts the eyes, promptly wash the eyes with large amounts of water, occasionally lifting the lower and upper lids. Get medical attention if any discomfort continues. Contact lenses should not be worn when working with this chemical. SKIN: If this chemical contacts the skin, flush the contaminated skin with water. Where there is evidence of skin irritation, get medical attention. INHALATION: If a person breathes large amounts of this chemical, move the exposed person to fresh air at once. Other measures are usually unnecessary. INGESTION: If this chemical has been swallowed, get medical attention immediately.										

V. DEACTIVITY/INICODIAATION						
V-REACTIVITY INFORMATION						
X STABLE UNSTABLE CONDITIONS TO AVOID None						
HAZARDOUS DECOMPOSITION PRODUCTS Mayliberate carbon monoxide or carbon dioxide.						
HAZARDOUS POLYMERZATION MAY OCCUR X OCCUR OCCUR Heat, sparks and open flame.						
INCOMPATIBILITY (Materials to avoid) Acids, oxidizing materials.						
VI-SPILL OR LEAK PROCEDURE INFORMATION						
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Stop the source of leak or release. Clean up releases as soon as possible, observing precautions in Special Protective Information. Contain liquid to prevent further contamination of soil, surface water or groundwater. Clean up small spills using appropriate techniques such as sorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Follow prescribed procedures for reporting and responding to larger releases.						
WASTE DISPOSAL METHODS Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations. Contact local environmental authorities for approved disposal of this material.						
VII-SPECIAL PROTECTION INFORMATION						
VENTILATION TYPE Local mechanical exhaust ventilation, capable of maintaining emissions at the point of use below the PEL.						
RESPIRATORY PROTECTION Wear a NIOSH-Approved respirator, appropriate for the concentration of vapor or mist encountered at the point of use.						
PROTECTIVE GLOVES Impervious EYE PROTECTION Wear eye protection to prevent any reasonable probability of eye contact.						
OTHER PROTECTIVE EQUIPMENT Wear appropriate equipment to prevent any repeated or prolonged skin contact.						
VIII - STORAGE AND HANDLING INFORMATION						
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE Keep out of reach of children. Store in a cool dry place away from incompatible materials. Keep container tightly closed when not in use. Workers should wash immediately when skin becomes contaminated. Work clothing should be changed daily if there is any possibility that the clothing may be contaminated. Remove clothing immediately if it is non-impervious clothing that becomes wet. The following equipment should be available: Eyewash, Quick drench. It is generally recognized that contact lenses should not be worn when working with chemicals because contact lenses may contribute to the severity of the injury.						
OTHER PRECAUTIONS Read and follow label instructions. The label contains information necessary for the proper use of the product. Containers, even those that have been emptied, will retain product residue and vapors. Always obey hazard warnings and handle empty containers as if they were full.						
IX-TOXICITY INFORMATION						
*HEALTH HAZARDS for Dipropylene Glycol Methyl Ether: INHALATION: Signs and symptoms of excessive exposure may be an esthetic or narcotic effects. EYE CONTACT: May cause slight transient (temporary) eye irritation: Corneal injury is unlikely. SKIN CONTACT: Prolonged exposure not likely to cause significant skin irritation. SKIN ABSORPTION: The LD50 for skin absorption in rabbits is greater than 20 ml/kg. Prolonged skin contact with very large amounts may cause drowsiness. SWALLOWING: Single dose oral toxicity is low. The oral LD50 for rats is 5.4 ml/kg. Small amounts swallowed incidental to normal handling operations are not likely to cause injury; swallowing amounts larger than that may cause injury. SYSTEMIC (OTHER TARGET ORGAN) EFFECTS: Observations in animals include minor liver or kidney effects. Signs and symptoms of excessive exposure may be an esthetic or narcotic effects.						
X-MISCELLANEOUS INFORMATION						
Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and the removal of the material from eyes, skin and clothing.						
PRODUCT CODE NA = NOT AVAILABLE DATE OF ISSUE SUPERSEDES SIGNED 012-0139 03-15-93 12-06-85						
The information contained herein is based on data considered accurate. However no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained						

thereof. They are offered solely for your consideration, investigation, and verification. Any use of these data and information must be determined by the user to be in accordance with applicable Federal, State and Local laws and regulations. KLEENCO PRODUCTS, INCORPORATED and its Distributors assume no responsibility for personal injury or property damage to vendees, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of the material.