FOR QUALITY, VALUE AND PERFORMANCE KLEENCO PRODUCTS, INC.		TELEPHONE NUMBER Reg. Phone 206-641-8888 For Emergency Assistance		e 38 sistance	HAZARD RATING 4 = EXTREME 3 = HIGH 2 = MODERATE 1 = SLIGHT 0 = INSIGNIFICANT to SEE SEE TONING				
• P.O. BOX 1786 • Bellevue, WA	Call Infotrac (800) 535-5053 0 = INSIGN *= SEE SI			EE SECTION I	v 📐	SPECIAL			
	MATER	IAL SA	FET	Y DAT	ra s	HEET			
PRODUCT NAME		DA	TE ISSUED	07-1	13-95	CODE	DOT HAZARD		
EFFORTLESS			PF	EPARED B	Y		-	Not	
FORMULA	AL NAMES AND	D OR SY	NONYMS		R. Silbaugh	008-0041	Regulated		
Proprietary Compound Cleaning Liquid									
I - COMPOSITIONAL INFORMATION/SARA III INFORMATION									
INGREDIENTS				CCUPATION EXPOSURE LIMITS V SHA PEL ACGIH TLV OTHER V			VAPOR PRESSUR mm Hg @ TEMP		
No toxic chemical(s) subject to the reporting requ will be provided to a physician in the event of a	medical emergency.						re is proprietary. A mor	e complete description	
II - PHYSICAL PROPERTY INFORMATION									
APPEARANCE and ODOR									
Water thin, clear pink liquid.	BOILING POINT			COATING V.O.C.			EVAPORATION RATE		
Not Applicable	340° to 2530° F.			Not Applicable		ble	Slower than ether		
SOLUBILITY IN WATER	SPECIFIC GRAVITY (Water = 1)		1)	VAPOR DENSITY					
Complete	1.0				t Applicat				
	III - FIRE	AND EXPLOS	SION H	iazard i	NFOR	MATION			
FLASH POINT AUTO IGNITIO		N TEMPERATURE		LOWER EXPLOSION LIMIT (%)		UPPER EXPLOSION LIMIT (%)			
Not Applicable	Not Available			Not Applicable		ole	Not Applicable		
EXTINGUISHING MEDIA	DRY CHEMICA		R SPRA	Y О	THER				
SPECIAL FIRE FIGHTING PROCEDURES For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment. This may include self-contained breathing apparatus to protect against the hazardous effects of normal products of combustion or oxygen deficiency. Read the entire MSDS.									
UNUSUAL FIRE AND EXPLOSION HAZ	ZARDS None kno	own							
	IV	- HEALTH H	474RD	INFORM		N			
THRESHOLD LIMIT VALUE ROUTI	-/>				-			N	
Not Established OF EN				X SKIN See Health Hazards			X See Health Hazards		
HEALTH HAZARDS (Acute and Chronic	) CHRONIC EFF	ECTS OF EXPOSL	JRE: None	known *See S	Section IX	ζ.			
CARCINOGENICITY: Not considered to be a carcinogen		IAR	graphs	Х	OSHA Regulated	ł			
SIGNS AND SYMPTOMS OF EXPOSU contact with the material may irritate the eyes.	RE INHALATION: N SKIN CONTACT: Pro	/apors and mist can longed or repeated	cause the contact m	following: - hea ay irritate the s	dache - n skin.	ausea - irritation of no	ose, throat, and lungs.	EYE CONTACT: Direct	
MEDICAL CONDITIONS GENERALLY	AGGRAVATED E	BY EXPOSURE	None k	nown.					
EMERGENCY AND FIRST AID PROCE upper lids. Get medical attention if any discomfor skin with water. Where there is evidence of skin once. Other measures are usually unnecessary	t continues. Contact l irritation, get medica	I attention. INHALA	TION: If a	person breathe	es large a	mounts of this chem	nts of water, occasiona nical contacts the skin, ical, move the expose	Ily lifting the lower and flush the contaminated d person to fresh air at	

V - REACTIVITY INFORMATION							
X STABLE UNSTABLE CONDITIONS TO AVOID None							
HAZARDOUS DECOMPOSITION PRODUCTS May liberate carbon monoxide or carbon dioxide.							
HAZARDOUS MAY WILL NOT CONDITIONS TO AVOID POLYMERIZATION OCCUR X OCCUR Heat, sparks and open flame.							
INCOMPATIBILITY (Materials to avoid) Acids, oxidizing materials.							
VI - SPILL OR LEAK PROCEDURE INFORMATION							
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Stop the source of leak or release. Clean up releases as soon as possible, observing precautions							
in Special Protective Information. Contain liquid to prevent further contamination of soil, surface water or groundwater. Clean up small spills using appropriate techniques such as sorben materials or pumping. Where feasible and appropriate, remove contaminated soil. Follow prescribed procedures for reporting and responding to larger releases.							
WASTE DISPOSAL METHODS Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations. Contact local environmental authorities for approved disposal of this material.							
VII - SPECIAL PROTECTION INFORMATION							
VENTILATION TYPE Local mechanical exhaust ventilation, capable of maintaining emissions at the point of use below the PEL.							
RESPIRATORY PROTECTION Wear a NIOSH-Approved respirator, appropriate for the concentration of vapor or mist encountered at the point of use.							
PROTECTIVE GLOVES Impervious EYE PROTECTION Wear eye protection to prevent any reasonable probability of eye contact.							
OTHER PROTECTIVE EQUIPMENT Wear appropriate equipment to prevent any repeated or prolonged skin contact.							
VIII - STORAGE AND HANDLING INFORMATION							
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE Keep out of reach of children. Store in a cool dry place away from incompatible materials. Keep containe tightly closed when not in use. Workers should wash promptly when skin becomes wet. The following equipment should be available: Eyewash. It is generally recognized that contact lenses should not be worn when working with chemicals because contact lenses may contribute to the severity of the injury.							
OTHER PRECAUTIONS Read and follow label instructions. The label contains information necessary for the proper use of the product. Containers, even those that have been emptied, will retain product residue and vapors. Always obey hazard warnings and handle empty containers as if they were full.							
IX - TOXICITY INFORMATION							
*HEALTH HAZARDS for Propylene Glycol n-Butyl Ether. INHALATION: Excessive exposure may cause irritation to upper respiratory tract. A single prolonged (hours) excessive inhalation exposure may cause adverse effects. Signs and symptoms of excessive exposure may be central nervous system effects. EYE CONTACT: May cause moderate eye irritation. May cause moderate cornear injury. SKIN CONTACT: Prolonged or repeated exposure may cause skin irritation. SKIN ABSORPTION: A single prolonged exposure may result in the material being absorbed in harmful amounts. The LD50 for skin absorption in rabbits is 1400 mg/kg. The liquid is reported to cause a burning sensation and itchiness at site of contact. Exposure to large amounts may produce anesthelic on narcotic effects. INGESTION: Single dose oral toxicity is low. The oral LD50 for rats is 3300 mg/kg. Small amounts swallowed incidental to normal handling operations are not likely to cause injury swallowing amounts larger than that may cause injury. SYSTEMIC (OTHER TARGET ORGAN) EFFECTS: Observations in animals include only increase liver size following repeated exposure TERATOLOGY (BIRTH DEFECTS): Birth defects are unlikely. Exposures having no adverse effects on the mother should have no effect on the fetus. REPRODUCTIVE EFFECTS: In animal studies, has been shown not to interfere with reproduction. MUTAGENICITY (EFFECTS ON GENETIC MATERIAL): Results of in vitro ('test tube') mutagenicity tests have been negative.							
X - MISCELLANEOUS INFORMATION							
Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and the removal of the material from eyes, skin and clothing							
PRODUCT CODE NA = NOT AVAILABLE DATE OF ISSUE SUPERSEDES SIGNED							
008-0041 07-13-95 Any previous MSDS							
The information contained herein is based on data considered accurate. However no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained thereof. They are offered solely for your consideration, investigation, and verification. Any use of these data and information must be determined by the user to be in accordance with applicable Federal, State and Local laws and regulations. KLEENCO PRODUCTS, INCORPORATED and its Distributors assume no responsibility for personal injury or property damage to vendees, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of the material.							