| KLEENCO PRODUCTS, INC.<br>• P.O. BOX 1786 • Bellevue, WA. 9800  | ANCE 206-<br>For Emerge         | . Phone<br>641-8888<br>ency Assistance<br>(800) 535-5053 | HAZARD RATING<br>4 = EXTREME<br>3 = HIGH<br>2 = MODERATE<br>1 = SLIGHT<br>0 = INSIGNIFICANT<br>* = SEE SECTION IN | тохісіту   | REACTIVITY<br>0<br>SPECIAL   |  |
|---|---------------------------------|--|---|--|--|--|
| MATERIAL SAFETY DATA SHEET  |                                 |  |   |  |  |  |
| PRODUCT NAME  |                                 | DATE ISSUED  | 07-18-95  | CODE   | DOT HAZARD   |  |
| PK-200 RTU  |                                 | PREPARED BY  | Dale R. Silbaugh  | 003-0111RT   | Not<br>Regulated   |  |
| Proprietary Compound Cleaning Liquid  |                                 |  |   |  |  |  |
| I - COMPOSITI   | CAS NUMBER                      | CCUPATION EX   | ARA III INI<br>KPOSURE LIMITS   | FORMATIO<br>VAPOR PRESSURE   | N<br>WEIGHT  |  |
| INGREDIENTS   | CAS NOMBER                      | OSHA PEL ACG   | IH TLV OTHER  | mm Hg @ TEMP   | PERCENT  |  |
| No toxic chemical(s) subject to the reporting requirements of section 313 of Tittle III and 40 CFR 342. <b>NOTE:</b> The precise composition of this mixture is proprietary. A more complete description will be provided to a physician in the event of a medical emergency.   |                                 |  |   |  |  |  |
| II - PHYSICAL PROPERTY INFORMATION  |                                 |  |   |  |  |  |
| APPEARANCE and ODOR<br>Water thin, clear purple liquid.   |                                 |  |   |  |  |  |
|   | NG POINT<br>340°F.              | COATING V  |   | EVAPORATION RATE   |  |  |
|   | IFIC GRAVITY (Water =           | 1) VAPOR DE  |   | Slowerth   | an etner   |  |
|   |                                 |  |   |  |  |  |
| III - FIRE AND EXPLOSION HAZARD INFORMATION   FLASH POINT AUTO IGNITION TEMPERATURE LOWER EXPLOSION LIMIT (%) UPPER EXPLOSION LIMIT (%)   |                                 |  |   |  |  |  |
| NotApplicable   | Not Available                   | -  | NotApplicable NotApplicable   |  |  |  |
| EXTINGUISHING MEDIA<br>X FOAM X CO2 X DRY CHEMICAL X WATER SPRAY OTHER  |                                 |  |   |  |  |  |
| SPECIAL FIRE FIGHTING PROCEDURES For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment. This may include self-contained breathing apparatus to protect against the hazardous effects of normal products of combustion or oxygen deficiency. Read the entire MSDS. |                                 |  |   |  |  |  |
| UNUSUAL FIRE AND EXPLOSION HAZARDS None known.  |                                 |  |   |  |  |  |
|   |                                 |  |   |  |  |  |
| IV - HEALTH HAZARD INFORMATION  |                                 |  |   |  |  |  |
| THRESHOLD LIMIT VALUE ROUTE(s) X INHALATION X SKIN X INGESTION   NotEstablished OF ENTRY: X See Health Hazards   HEALTH HAZARDS (Acute and Chronic) CHRONIC EFFECTS OF EXPOSURE: None known *See Section IX. See Health Hazards      |                                 |  |   |  |  |  |
| CARCINOGENICITY: NTP IARC Monographs X OSHA Regulated   |                                 |  |   |  |  |  |
| SIGNS AND SYMPTOMS OF EXPOSURE INHALATION: Vapors and mist can cause the following: - headache - nausea - irritation of nose, throat, and lungs. EYE CONTACT: Direct contact with the material may irritate the eyes. SKIN CONTACT: Prolonged or repeated contact may irritate the skin.  |                                 |  |   |  |  |  |
| MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE None Known.   |                                 |  |   |  |  |  |
| EMERGENCY AND FIRST AID PROCEDURE<br>upper lids. Get medical attention if any discomfort continu<br>skin with water. Where there is evidence of skin irritation<br>once. Other measures are usually unnecessary. INGES  | , get medical attention. INHALA | ATION: If a person breathes                              | s large amounts of this chem  | ts of water, occasionally<br>ical contacts the skin, flu<br>ical, move the exposed | lifting the lower and<br>sh the contaminated<br>person to fresh air at |  |

| V - REACTIVITY INFORMATION   |  |  |  |  |  |
|--|--|--|--|--|--|
| X STABLE UNSTABLE CONDITIONS TO AVOID None   |  |  |  |  |  |
| HAZARDOUS DECOMPOSITION PRODUCTS May liberate carbon monoxide or carbon dioxide.   |  |  |  |  |  |
| HAZARDOUS MAY WILL NOT CONDITIONS TO AVOID   |  |  |  |  |  |
| POLYMERIZATION OCCUR X OCCUR Heat, sparks and open flame.   INCOMPATIBILITY (Materials to avoid) Acids, oxidizing materials.   |  |  |  |  |  |
|  |  |  |  |  |  |
| VI - SPILL OR LEAK PROCEDURE INFORMATION   |  |  |  |  |  |
| STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Stop the source of leak or release. Clean up releases as soon as possible, observing precautions in Special Protective Information. Contain liquid to prevent further contamination of soil, surface water or groundwater. Clean up small spills using appropriate techniques such as sorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Follow prescribed procedures for reporting and responding to larger releases.  |  |  |  |  |  |
| WASTE DISPOSAL METHODS Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations. Contact local environmental authorities for approved disposal of this material.  |  |  |  |  |  |
| VII - SPECIAL PROTECTION INFORMATION   |  |  |  |  |  |
| VENTILATION TYPE Local mechanical exhaust ventilation, capable of maintaining emissions at the point of use below the PEL.   |  |  |  |  |  |
| RESPIRATORY PROTECTION Wear a NIOSH-Approved respirator, appropriate for the concentration of vapor or mist encountered at the point of use.   |  |  |  |  |  |
| PROTECTIVE   GLOVES   Impervious   EYE   PROTECTION   Wear eye protection to prevent any reasonable probability of eye contact.  |  |  |  |  |  |
| OTHER PROTECTIVE EQUIPMENT Wear appropriate equipment to prevent any repeated or prolonged skin contact.   |  |  |  |  |  |
| VIII - STORAGE AND HANDLING INFORMATION  |  |  |  |  |  |
| PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE Keep out of reach of children. Store in a cool dry place away from incompatible materials. Keep container tightly closed when not in use. Workers should wash promptly when skin becomes wet. The following equipment should be available: Eyewash. It is generally recognized that contact lenses should not be worn when working with chemicals because contact lenses may contribute to the severity of the injury.   |  |  |  |  |  |
| OTHER PRECAUTIONS Read and follow label instructions. The label contains information necessary for the proper use of the product. Containers, even those that have been emptied, will retain product residue and vapors. Always obey hazard warnings and handle empty containers as if they were full.   |  |  |  |  |  |
| IX - TOXICITY INFORMATION  |  |  |  |  |  |
| *HEALTH HAZARDS for Propylene Glycoln-Butyl Ether. INHALATION: Excessive exposure may cause irritation to upper respiratory tract. A single prolonged (hours) excessive inhalation exposure may cause adverse effects. Signs and symptoms of excessive exposure may be central nervous system effects. EYE CONTACT: May cause moderate eye irritation. May cause moderate corneal injury. SKIN CONTACT: Prolonged or repeated exposure may cause skin irritation. SKIN ABSORPTION: A single prolonged exposure to may result in the material being absorbed in harmful amounts. The LD50 for skin absorption in rabbits is 1400 mg/kg. The liquid is reported to cause a burning sensation and itchiness at site of contact. Exposure to large amounts may produce anesthetic or narcotic effects. INGESTION: Single dose oral toxicity is low. The oral LD50 for rats is 3300 mg/kg. Small amounts swallowed incidental to normal handling operations are not likely to cause injury; swallowing amounts larger than that may cause injury. SYSTEMIC (OTHER TARGET ORGAN) EFFECTS: Observations in animals include only increase liver size following repeated exposure. TERATOLOGY (BIRTH DEFECTS): Birth defects are unlikely. Exposures having no adverse effects on the mother should have no effect on the fetus. REPRODUCTIVE EFFECTS: In animal studies, has been shown not to interfere with reproduction. MUTAGENICITY (EFFECTS ON GENETIC MATERIAL): Results of in vitro ('test tube') mutagenicity tests have been negative. |  |  |  |  |  |
| X - MISCELLANEOUS INFORMATION  |  |  |  |  |  |
| Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and the removal of the material from eyes, skin and clothing.  |  |  |  |  |  |
|  |  |  |  |  |  |
| PRODUCT CODE NA = NOT AVAILABLE DATE OF ISSUE SUPERSEDES SIGNED  |  |  |  |  |  |
|  |  |  |  |  |  |
| The information contained herein is based on data considered accurate. However no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained thereof. They are offered solely for your consideration, investigation, and verification. Any use of these data and information must be determined by the user to be in accordance with applicable Federal, State and Local laws and regulations. KLEENCO PRODUCTS, INCORPORATED and its Distributors assume no responsibility for personal injury or property damage to vendees, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of the material.   |  |  |  |  |  |
| PAGE 2 - 003-0111RT  |  |  |  |  |  |