	[®]	TELEPHO	NE NUN	/IBER	HAZARD RATI	NG	FIRE	<u> </u>	
KLEENCO		Reg. Phone 206-641-8888			4 = EXTREME 3 = HIGH 2 = MODERATE				
FOR QUALITY, VALUE AND PERFORMANCE		For Emergency Assitance Call Infotrac (800) 535-5053			1 = SLIGHT 0 = INSIGNIFICA	_{NT} тох	хісіту		
• P.O. BOX 1786 • Bellevue, WA					* = SEE SECTION			SPECIAL	
MATERIAL SAFETY DATA SHEET									
RETAIN "WB" R.T.U				ISSUE		C	ODE	DOT HAZARD Not	
FORMULA		AL NAMES AN			Dale R. Silbaugh		007-0297	Regulated	
I-COMPOSITIONAL INFORMATION/SARA III INFORMATION									
		NUMBER OCCUPATION EXPOUSURE LIMITS OSHA PEL ACGIH TLV OTHER				VAF	VAPOR PRESSURE WEIGHT mm Hg @ TEMP PERCENT		
			0011/1		on tev onek			TEROENT	
No toxic chemical(s) subject to the reporting requirements of section 313 of Tittle III and 40 CFR 342. NOTE: The precise composition of this mixture is proprietary. A more complete description will be provided to a physician in the event of a medical emergency.									
II-PHYSICAL PROPERTY INFORMATION									
APPEARANCE and ODOR Slightly viscous, opaque tan liquid with mild acry	lic odor.								
MELTING POINT NotApplicable	BOILING POIN	IT °F @ 760 mm Hg.	C	COATING V.O.C. NotApplicable			EVAPORATION Slower th		
SOLUBILITY IN WATER	SPECIFIC GRA	1) V	APOR DENSITY			Slower undirettier			
Dispersible 1.08 Not Applicable III - FIRE AND EXPLOSION HAZARD INFORMATION									
FLASH POINT AUTO IGNITION TEMPERATURE LOWER EXPLOSION LIMIT (%) UPPER EXPLOSION LIMIT (%)								SION LIMIT (%)	
NotApplicable Not A		Available	vailable Not Applicable			Not Applicable			
X FOAM X CO2 X DRY CHEMICAL X WATER SPRAY OTHER									
SPECIAL FIRE FIGHTING PROCEDURES For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment. This may include self-contained breathing apparatus to protect against the hazardous effects of normal products of combustion or oxygen deficiency. Read the entire MSDS.									
UNUSUAL FIRE AND EXPLOSION HAZARDS Heating above 392°F or in fire conditions toxic decomposition products may be formed. These products may cause severe eye, nose, throat and lung irritation. Use adequate ventilation.									
IV-HEALTH HAZARD INFORMATION									
THRESHOLD LIMIT VALUE ROUTE		HALATION					X INGESTION		
AEL* (Du Pont) 10 mg/m3 - 8 Hr. OF EN HEALTH HAZARDS (Acute and Chronic	TRY:	See Health Hazard		Se	e Health Hazards	/	See Health Ha	zards	
CARCINOGENICITY: Not considered to be a carcinogen	NTP	IAF	RC Monogra	phs	X OSHA Regula	ated			
SIGNS AND SYMPTOMS OF EXPOSURE EYE CONTACT: May initially include eye irritation with discomfort, tearing, or blurring of vision. SKIN CONTACT: May include skin irritation with discomfort or rash; allergic skin rashes. Data to evaluate the skin permeation hazard of this compound are insufficient. There are no reports of human sensitization. INHALATION: Inhalation may initially include irritation of the upper respiratory passages; or temporary lung irritation effects with cough, discomfort, difficulty breathing, or shortness of breath. SWALLOWED: No information available.									
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE Individuals with preexisting diseases of the lungs may have increased susceptibility to the toxicity of excessive exposures.									
EMERGENCY AND FIRST AID PROCE physician. EYES: In case of contact, immediately Wash contaminated clothing before reuse. INGE Call a physician. NOTESTO PHYSICIAN: Activa thoroughly. Administer 5mL/kg, or 350 mL for an	ited charcoal slurry n	TION: If inhaled, re ty of water for at lea , do not induce vom nay be administered	move to fresh a ist 15 minutes. iting. Immedia d. To prepare a	air. If not bi Call a phy tely give tw ctivated ch	reathing, give artificial respi sician. SKIN: In case of cont vo glasses of water. Never gi narcoal slurry, suspend 50 g	ration. If act, imm ve anyth rams act	breathing is difficult nediately wash skin ning by mouth to an u tivated charcoal in 4	, give oxygen. Call a with soap and water. nconscious person. 00mL water and mix	

V-REACTIVITY INFORMATION								
X STABLE UNSTABLE CONDITIONS TO AVOID None								
HAZARDOUS DECOMPOSITION PRODUCTS Heating above 392°F or infire conditions toxic decomposition products may be formed. These products may cause severe eye, nose, throat and lung irritation. Use adequate ventilation.								
HAZARDOUS MAY WILL NOT CONDITIONS TO AVOID POLYMERZATION OCCUR X OCCUR None known.								
INCOMPATIBILITY (Materials to avoid) Incompatible with cations.								
VI - SPILL OR LEAK PROCEDURE INFORMATION								
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Stop the source of leak or release. Clean up releases as soon as possible, observing precautions in Special Protective Information. Contain liquid to prevent further contamination of soil, surface water or groundwater. Clean up small spills using appropriate techniques such as sorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Follow prescribed procedures for reporting and responding to larger releases.								
WASTE DISPOSAL METHODS Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations. Contact local environmental authorities for approved disposal of this material.								
VII - SPECIAL PROTECTION INFORMATION								
VENTILATION TYPE Use only with adequate ventilation. Keep container tightly closed. Vent dryer fumes outside work area. Do not aerosolize. In spray applications, use airless type pressure spray equipment at less than 60 psi and exhaust ducts, drip pans, or other design features to minimize worker exposure to mists and overspray. Keep away from open flames and heated surfaces above 392°F.								
RESPIRATORY PROTECTION Wear a NIOSH-Approved respirator, appropriate for the concentration of vapor or mist encountered at the point of use.								
PROTECTIVE GLOVES EYE PROTECTION Wear eye protection to prevent any reasonable probability of eye contact.								
OTHER PROTECTIVE EQUIPMENT Wear appropriate equipment to prevent any repeated or prolonged skin contact.								
VIII - STORAGE AND HANDLING INFORMATION								
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE Avoid circumstances that produce respirable particles unless suitable ventilation and protective equipment is used. Store in a cool dry place away from incompatible materials. Keep container tightly closed when not in use. Workers should wash promptly when skin becomes wet. The following equipment should be available: Eyewash. It is generally recognized that contact lenses should not be worn when working with chemicals because contact lenses may contribute to the severity of the injury.								
OTHER PRECAUTIONS								
Read and follow label instructions. The label contains information necessary for the proper use of the product. Containers, even those that have been emptied, will retain product residue and vapors. Always obey hazard warnings and handle empty containers as if they were full.								
IX - TOXICITY INFORMATION								
On the basis of available information this material does not appear to possess any toxicological properties which would require special handling other than good industrial hygiene and safety practices employed with any industrial chemical.								
X-MISCELLANEOUS INFORMATION								
Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and the removal of the material from eyes, skin and clothing.								
PRODUCT CODE NA = NOT AVAILABLE DATE OF ISSUE SUPERSEDES SIGNED								
007-0297 04-12-93 All previous MSDS The information contained herein is based on data considered accurate. However no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained thereof. They are offered solely for your consideration, investigation, and verification. Any use of these data and information must be determined by the user to be in accordance with applicable Federal, State and Local laws and regulations. KLEENCO PRODUCTS, INCORPORATED and its Distributors assume no responsibility for personal injury or property damage to vendees, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of the material.								