

TELEPHONE NUMBER Reg. Phone 206-641-8888

For Emergency Assitance Call Infotrac (800) 535-5053

HAZARD **RATING** FIRE 0 = EXTREME REACTIVITY = HIGH 0 = MODERATE = SLIGHT 0 = INSIGNIFICANT

SPECIAL P.O. BOX 1786 Bellevue, WA. 98009 SEE SECTION IV MATERIAL SAFI PRODUCT NAME CODE DOT HAZARD STAT-7AP PREPARED BY Not Regulated Dale R. Silbaugh 007-0139 FORMULA CHEMICAL NAMES AND OR SYNONYMS Compound Cleaning Liquid Proprietary I-COMPOSITIONAL INFORMATION/SARA III INFORMATION OCCUPATION EXPOUSURE ACGIH TLV LIMITS APOR PRESSURE mm Hg @ TEMP WEIGHT PERCENT VAPOR CAS NUMBER **INGREDIENTS** OSHA PEL OTHER Isopropanol 67-63-0 400 PPM 400 PPM None 33.0 68°F No toxic chemical(s) subject to the reporting requirements of section 313 of Tittle III and 40 CFR 342. NOTE: The precise composition of this mixture is proprietary. A more complete description will be provided to a physician in the event of a medical emergency II-PHYSICAL PROPERTY INFORMATION APPEARANCE and ODOR Viscous, clear liquid. MELTING POINT BOILING POINT COATING V.O.C. **EVAPORATION RATE** Not Applicable 181°F Not Applicable Slower than ether SOLUBILITY IN WATER SPECIFIC GRAVITY (Water = 1) VAPOR DENSITY 1.0 Not Applicable Complete III-FIRE AND EXPLOSION HAZARD INFORMATION FLASH POINT AUTO IGNITION TEMPERATURE LOWER EXPLOSION LIMIT (%) UPPER EXPLOSION LIMIT (%) Not Applicable Not Available Not Applicable Not Applicable EXTINGUISHING MEDIA Χ Χ Χ **FOAM** C O₂ DRY CHEMICAL WATER SPRAY OTHER SPECIAL FIRE FIGHTING PROCEDURES For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment. This may include self-contained breathing apparatus to protect against the hazardous effects of normal products of combustion or oxygen deficiency. Read the entire MSDS. UNUSUAL FIRE AND EXPLOSION HAZARDS May be slippery, avoid walking on spilled material. IV-HEALTH HAZARD INFORMATION THRESHOLD LIMIT VALUE ROUTE(s) INHALATION SKIN INGESTION Χ Χ Χ OF ENTRY: Not Established See Health Hazards See Health Hazards See Health Hazards HEALTH HAZARDS (Acute and Chronic) CHRONIC EFFECTS OF EXPOSURE: Contains Pine Oil which is a weak skin allergen. *See Section IX. CARCINOGENICITY: NTP OSHA Regulated IARC Monographs Not considered to be a carcinogen SIGNS AND SYMPTOMS OF EXPOSURE INHALATION: Breathing mists and vapors may irritate the nose and throat and cause coughing and chest discomfort. EYE CONTACT: Liquids and mist may irritate the eyes. SKIN CONTACT: No irritation is likely after brief contact but may be irritating after prolonged contact. MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

EMERGENCY AND FIRST AID PROCEDURES EYES: If this chemical contacts the eyes, immediately wash the eyes with large amounts of water, occasionally lifting the lower and upper lids. Get medical attention immediately. Contact lenses should not be worn when working with this chemical. SKIN: If this chemical contacts the skin, flush the contaminated skin with water promptly. If this chemical penetrates the clothing, immediately remove the clothing and flush the skin with water promptly. If irritation persists after washing, get medical attention. Launder clothing before reuse. INHALATION: If a person breathes large amounts of this chemical, move the exposed person to fresh air at once. Other measures are usually unnecessary. INGESTION: If this chemical has been swallowed, get medical attention immediately.

None known.

V DEACTIVITY INFORMATION
V-REACTIVITY INFORMATION CONDITIONS TO AVOID None
X STABLE UNSTABLE
HAZARDOUS DECOMPOSITION PRODUCTS May liberate carbon monoxide or carbon dioxide.
HAZARDOUS MAY WILL NOT CONDITIONS TO AVOID POLYMERZATION OCCUR X OCCUR Heat, sparks and open flame.
INCOMPATIBILITY (Materials to avoid) Acids, oxidizing materials.
VI - SPILL OR LEAK PROCEDURE INFORMATION
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Stop the source of leak or releases. Clean up releases as soon as possible, observing precautions
in Special Protective Information. Contain liquid to prevent further contamination of soil, surface water or groundwater. Clean up small spills using appropriate techniques such as sorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Follow prescribed procedures for reporting and responding to larger releases.
WASTE DISPOSAL METHODS Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations. Contact local environmental authorities for approved disposal of this material.
VII-SPECIAL PROTECTION INFORMATION
VENTILATION TYPE Local mechanical exhaust ventilation, capable of maintaining emissions at the point of use below the PEL.
2004 month of a continuous continuous continuous continuous and a continuous action point of a continuous action a
RESPIRATORY PROTECTION Wear a NIOSH-Approved respirator, appropriate for the concentration of vapor or mist encountered at the point of use.
PROTECTIVE GLOVES Impervious EYE PROTECTION Wear eye protection to prevent any reasonable probability of eye contact.
OTHER PROTECTIVE EQUIPMENT Wear appropriate equipment to prevent any repeated or prolonged skin contact.
VIII - STORAGE AND HANDLING INFORMATION
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE Keep out of reach of children. Store in a cool dry place away from incompatible materials. Keep container
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE Keep out of reach of children. Store in a cool dry place away from incompatible materials. Keep container tightly closed when not in use. Workers should wash promptly when skin becomes wet. The following equipment should be available: Eyewash. It is generally recognized that contact lenses should not be worn when working with chemicals because contact lenses may contribute to the severity of the injury.
tightly closed when not in use. Workers should wash promptly when skin becomes wet. The following equipment should be available: Eyewash. It is generally recognized that contact lenses should not be worn when working with chemicals because contact lenses may contribute to the severity of the injury. OTHER PRECAUTIONS Read and follow label instructions. The label contains information necessary for the proper use of the product. Containers, even those that have been emptied,
tightly closed when not in use. Workers should wash promptly when skin becomes wet. The following equipment should be available: Eyewash. It is generally recognized that contact lenses should not be worn when working with chemicals because contact lenses may contribute to the severity of the injury.
tightly closed when not in use. Workers should wash promptly when skin becomes wet. The following equipment should be available: Eyewash. It is generally recognized that contact lenses should not be worn when working with chemicals because contact lenses may contribute to the severity of the injury. OTHER PRECAUTIONS Read and follow label instructions. The label contains information necessary for the proper use of the product. Containers, even those that have been emptied,
tightly closed when not in use. Workers should wash promptly when skin becomes wet. The following equipment should be available: Eyewash. It is generally recognized that contact lenses should not be worn when working with chemicals because contact lenses may contribute to the severity of the injury. OTHER PRECAUTIONS Read and follow label instructions. The label contains information necessary for the proper use of the product. Containers, even those that have been emptied, will retain product residue and vapors. Always obey hazard warnings and handle empty containers as if they were full.
tightly closed when not in use. Workers should wash promptly when skin becomes wet. The following equipment should be available: Eyewash. It is generally recognized that contact lenses should not be worn when working with chemicals because contact lenses may contribute to the severity of the injury. OTHER PRECAUTIONS Read and follow label instructions. The label contains information necessary for the proper use of the product. Containers, even those that have been emptied, will retain product residue and vapors. Always obey hazard warnings and handle empty containers as if they were full. IX - TOXICITY INFORMATION
tightly closed when not in use. Workers should wash promptly when skin becomes wet. The following equipment should be available: Eyewash. It is generally recognized that contact lenses should not be worn when working with chemicals because contact lenses may contribute to the severity of the injury. OTHER PRECAUTIONS Read and follow label instructions. The label contains information necessary for the proper use of the product. Containers, even those that have been emptied, will retain product residue and vapors. Always obey hazard warnings and handle empty containers as if they were full. IX - TOXICITY INFORMATION TOXICITY: ORAL - No data found. DERMAL - No data found. INHALATION: No data found. "HEALTH HAZARDS for Isopropanol: ACUTE HEALTH EFFECTS: INHALATION - Vapors and mists irritate the nose and throat. Inhalation of higher concentrations may cause headaches, vomiting, and coma. Inhalation of very high concentrations or prolonged exposure may cause unconsciousness or death. EYE CONTACT: Vapors will irritate the eyes. Liquid and mists can severely irritate to or damage the eyes and cause corneal burns. SKIN CONTACT: Brief contact may dry the skin, or cause burning sensation. Prolonged or repeated contact may dry the skin, or cause burning sensation. Prolonged or repeated contact may dry the skin, or cause burning sensation. Prolonged or repeated contact may dry the skin, or cause burning sensation. Prolonged or repeated contact may dry the skin, or cause burning and nethans unconsciousness or death
tightly closed when not in use. Workers should wash promptly when skin becomes wet. The following equipment should be available: Eyewash. It is generally recognized that contact lenses should not be worn when working with chemicals because contact lenses may contribute to the severity of the injury. OTHER PRECAUTIONS Read and follow label instructions. The label contains information necessary for the proper use of the product. Containers, even those that have been emptied, will retain product residue and vapors. Always obey hazard warnings and handle empty containers as if they were full. IX - TOXICITY INFORMATION TOXICITY: ORAL - No data found. DERMAL - No data found. INHALATION: No data found. *HEALTH HAZARDS for Isopropanol: ACUTE HEALTH EFFECTS: INHALATION - Vapors and mists irritate the nose and throat. Inhalation of higher concentrations may cause headaches, vomiting, and coma. Inhalation of very high concentrations or prolonged exposure may cause unconsciousness or death. EYE CONTACT: Vapors will irritate the eyes. Liquid and mists can severely irritate or dramage the eyes and cause corneal burns. SKIN CONTACT: Brief contact may dry the skin, or cause burning or stinging sensation. Prolonged or repeated contact may irritate the skin, causing dermatitis. SWALLOWED: Swallowing large quantities causes headaches, nausea, vomiting, stomach cramps and diarrhea, and perhaps unconsciousness, or death. CHRONIC EFFECTS OF EXPOSURE: Prolonged or repeated exposure to high concentrations can produce severe or fatal CNS depression. MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Persons with pre-existing skin disorders, eye problems, or impaired respiratory function may be more susceptible to the effects of this substance.
itightly closed when not in use. Workers should wash promptly when skin becomes welf. The following equipment should be available: Eyewash. It is generally recognized that confact lenses should not be worn when working with chemicals because contact lenses may contribute to the severity of the injury. OTHER PRECAUTIONS Read and follow label instructions. The label contains information necessary for the proper use of the product. Containers, even those that have been emptied, will retain product residue and vapors. Always obey hazard warnings and handle empty containers as if they were full. IX - TOXICITY INFORMATION TOXICITY: ORAL - No data found. DERMAL - No data found. INHALATION: No data found. "HEALTH HAZARDS for Isopropanol: ACUTE HEALTH EFFECTS: INHALATION - Vapors and mists irritate the nose and throat. Inhalation of higher concentrations may cause headaches, vomiting, and coma. Inhalation of very high concentrations or prolonged exposure may cause unconsciousness or death. EYE CONTACT: Vapors will irritate the eyes. Liquid and mists can severely irritate or damage the eyes and cause corneal burns. SKIN CONTACT: Brief contact may dry the skin, or cause burning or stinging sensation. Prolonged or repeated contact may irritate the skin, causing demaititis. SWALLOWED: Swallowing large quantities causes headaches, ususea, womiting, stomach cramps and diarrhea, and perhaps unconsciousness, or death. CHRONIC EFFECTS OF EXPOSURE: Prolonged or repeated exposure to high concentrations can produce severe or fatal CNS depression. MEDICAL CONDITIONS CENERALLY AGGRAVATED BY EXPOSURE: Persons with pre-existing skin disorders, eye problems, or impaired respiratory function may be more susceptible to the effects of this substance. X-MISCELLANEOUS INFORMATION Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and the removal of the material from eyes, skin and clothing.
ightly closed when not in use. Workers should wash promptly when skin becomes wet. The following equipment should be available: Eyewash. It is generally recognized that confact lenses should not be worn when working with chemicals because contact lenses may contribute to the severity of the injury. OTHER PRECAUTIONS Read and follow label instructions. The label contains information necessary for the proper use of the product. Containers, even those that have been emptied, will retain product residue and vapors. Always obey hazard warnings and handle empty containers as if they were full. IX - TOXICITY INFORMATION TOXICITY: ORAL - No data found. DERMAL - No data found. INHALATION: No data found. "HEALTH HAZARDS for Isopropanal: ACUTE HEALTH EFFECTS: INHALATION - Vapors and mists irritate the nose and throat. Inhalation of higher concentrations may cause headaches, rownling, and coma. Inhalation of very high concentrations or prolonged exposure may cause unconsciousness or death. EYE CONTACT: Vapors will irritate the eyes. Liquid and mists can severely irritate or damage the eyes and cause corneal burns. SKIN CONTACT: Brief contact may dry the skin, or cause burning or stinging sensation. Prolonged or repeated contact may irritate the skin, causing dermalitis. SWALLOWED: Swallowing large quantities causes headaches, nausea, vorniting, shomach cramps and diarrhea, and perhaps unconsciousness, or death. CHRONIC EFFECTS OF EXPOSURE: Persons with pre-existing skin disorders, eye problems, or impaired respiratory function may be more susceptible to the effects of this substance. X-MISCELLANEOUS INFORMATION Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and the removal of the material from eyes, skin and clothing. This material may be slippery when spilled on hard surfaces.
ightly closed when not in use. Workers should wash promptly when skin becomes wet. The following equipment should be available: Eyewash. It is generally recognized that confact lenses should not be worn when working with chemicals because contact lenses may contribute to the severity of the injury. OTHER PRECAUTIONS Read and follow label instructions. The label contains information necessary for the proper use of the product. Containers, even those that have been emptied, will retain product residue and vapors. Always obey hazard warnings and handle empty containers as if they were full. IX - TOXICITY INFORMATION TOXICITY: ORAL - No data found. DERMAL - No data found. INHALATION: No data found. "HEALTHHAZARDS for Isopropanol: ACUTE HEALTHEFFECTS: INHALATION - Vapors and mists irritate the nose and throat. Inhalation of higher concentrations may cause headaches, vomiting, and coma. Inhalation of very high concentrations or prolonged exposure may cause unconsciousness or death. EYE CONTACT: Vapors will irritate the eyes. Liquid and mists can severely irritate or damage the eyes and cause corneal burns. SkiN CONTACT: Brief contact may dry the skin, or cause burning or stinging sensation. Prolonged or repeated contact may rittate the skin, causing dermalitis. SWALLOWED: Swallowing large quantilities causes headaches, nause, vomiting, stomach cramps and diarrhea, and perhaps unconsciousness, or death. CHRONIC EFFECTS OF EXPOSURE: Prolonged or repeated exposure to high concentrations can produce severe or fatal CNS depression. MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Persons with pre-existing skin disorders, eye problems, or impaired respiratory function may be more susceptible to the effects of this substance. X - MISCELLANEOUS INFORMATION Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and the removal of the material from eyes, skin and clothing. This material may be slippery when spilled on hard surfaces.